

U.S. Serial No. 10/710,306  
Examiner: Steven J. Ganey  
Art Unit No.: 3752  
Page 4 of 12

Atty. Docket No.: JD-327A-US

RECEIVED  
CENTRAL FAX CENTER  
AUG 31 2006

IN THE CLAIMS

Please amend the claims as follows:

1. (Currently Amended) An apparatus for supporting a hand held liquid dispensing device comprising:  
[[a]] at least one first support member for receiving a nozzle portion of the dispensing device; and  
[[a]] at least one second support member for holding a container, the at least first and second support members being spaced from each other in substantial axial alignment and connected to a frame member for connection to a supporting structure[[.]] the at least first support member constructed and arranged to facilitate the filling of the container when the nozzle portion is placed in the at least first support member and a container is placed on the at least second support member in one instance and the at least second support member being displaceable in another instance to provide a hose connection to the nozzle portion for filling of a bucket.
2. (Currently Amended) The apparatus as defined in Claim 1 wherein the at least one first support member includes a cavity.
3. (Currently Amended) The apparatus as defined in Claim 1 wherein the at least one second support member is pivotably connected to the frame member.
4. (Currently Amended) The apparatus as defined in Claim 1 wherein there are two oppositely disposed at least one first support members connected to the frame member.
5. (Currently Amended) The apparatus as defined in Claim 1 wherein the at least one first support member is defined by a platform having a cavity for placement of a dispenser ~~nozzle therein~~ the nozzle portion of the dispensing device therein.

U.S. Serial No. 10/710,306  
Examiner: Steven J. Ganey  
Art Unit No.: 3752  
Page 5 of 12

Atty. Docket No.: JD-327A-US

6. (Currently Amended) The apparatus as defined in Claim 1 wherein the at least one second support member is defined by a foot portion, the foot portion supported by the frame and pivotally connected to the frame member.

7. (Original) The apparatus as defined in Claim 6 wherein the foot portion includes a concave portion for receiving a bottle.

8. (Currently Amended) The apparatus as defined in Claim 1 wherein there are two oppositely disposed at least one second support members connected to the frame member, the frame member defined by a first portion extending in a first direction and a second portion extending essentially at right angles to the first portion, the second portion connected to the two oppositely disposed second support members.

9. (Original) The apparatus as defined in Claim 8 wherein the frame member is composed of rod members.

10. (Currently Amended) The apparatus as defined in Claim ~~[[1]]~~ 2 wherein the cavity includes a passage constructed and arranged to permit passage of the nozzle portion therethrough.

11. (Currently Amended) A combined hand held liquid dispensing device and apparatus for supporting the device comprising:  
a liquid dispensing device;  
~~[[a]]~~ at least one first support member receiving a nozzle portion of the dispensing device; and  
~~[[a]]~~ at least one second support member for holding a container, the at least first and second support members being spaced from each other in substantial axial alignment and connected to a frame member for connection to a supporting structure~~[[.]]~~ the at least first support member constructed and arranged to facilitate the filing of the container when the nozzle portion is placed in the at least first support member and a container is placed on the at least

**U.S. Serial No. 10/710,306**  
Examiner: Steven J. Ganey  
Art Unit No.: 3752  
Page 6 of 12

**Atty. Docket No.: JD-327A-US**

second support member in one instance and the at least second support member being displaceable in another instance to provide a hose connection to the nozzle portion for filling of a bucket.

12. (Currently Amended) The apparatus as defined in Claim 11 wherein the at least one first support member includes a cavity.

13. (Currently Amended) The apparatus as defined in Claim 11 wherein the at least one second support member is pivotally connected to the frame member.

14. (Original) The apparatus as defined in Claim 11 wherein there are two oppositely disposed first support members connected to the frame member.

15. (Currently Amended) The apparatus as defined in Claim 11 wherein the at least one first support member is defined by a platform having a cavity for placement of ~~[a dispenser nozzle therein]~~ the nozzle portion of the dispensing device therein.

16. (Currently Amended) The apparatus as defined in Claim 11 wherein the at least one second support member is defined by a foot portion, the foot portion supported by the frame and pivotally connected to the frame member.

17. (Original) The apparatus as defined in Claim 16 wherein the foot portion includes a concave portion for receiving a bottle.

18. (Currently Amended) The apparatus as defined in Claim 11 wherein there are two oppositely disposed at least one second support members connected to the frame member, the frame member defined by a first portion extending in a first direction and a second portion extending essentially at right angles to the first portion, the second portion connected to the two oppositely disposed second support members.

**U.S. Serial No. 10/710,306**  
Examiner: Steven J. Ganey  
Art Unit No.: 3752  
Page 7 of 12

**Atty. Docket No.: JD-327A-US**

19. (Original) The apparatus as defined in Claim 18 wherein the frame member is composed of rod members.

20. (Currently Amended) The apparatus as defined in Claim ~~[[11]]~~ 12 wherein the cavity includes a passage constructed and arranged to permit passage of the nozzle portion therethrough.

21. (Currently Amended) An apparatus for supporting a hand held liquid dispensing device comprising:

[[a]] at least one first support member for receiving a nozzle portion of the dispensing device; and

[[a]] at least one second support member for holding a container, the at least first and second support members being spaced from each other in substantial axial alignment and connected to a frame member for connection to a supporting structure, the frame member including [[a]] at least one third support member for the dispensing device~~[[.]] the at least one first support member constructed and arranged to facilitate the filing of the container when the nozzle portion is placed in the at least one first support member and a container is placed on the at least one second support member in one instance and the at least one second support member being displaceable in another instance to provide a hose connection to the nozzle portion for filling of a bucket.~~

22. (Currently Amended) The apparatus as defined in Claim 21 wherein the frame member includes [[a]] at least one side portion connected to the at least one third support member.

23. (Currently Amended) The apparatus as defined in Claim 22 wherein the at least one side portion angles inwardly in a direction from the at least one third support member toward the at least one first support member.

24. (Cancelled)

**U.S. Serial No. 10/710,306**  
Examiner: Steven J. Ganey  
Art Unit No.: 3752  
Page 8 of 12

**Atty. Docket No.: JD-327A-US**

25. (Original) The apparatus as defined in Claim 21 wherein there are two oppositely disposed first, second and third support members connected to the frame member.

26. (Currently Amended) The apparatus as defined in Claim 21 wherein the at least one second support member is pivotally connected to the frame member.

27. (Cancelled)

28. (New) An apparatus for supporting a hand held liquid dispensing device comprising:  
at least one first support member for receiving a nozzle portion of the dispensing device;  
at least one second support member for holding a container, the first and second at least one support members being spaced from each other in substantial axial alignment and connected to a frame member for connection to a supporting structure, the at least one second support member being pivotally connected to the frame member, the frame member including at least one third support member for the dispensing device; and  
a funnel for placement in the at least one first support member and the at least one second support member being pivotally connected to the frame member.

29. (New) An apparatus for supporting a hand held liquid dispensing device comprising:  
at least one first support member for receiving a nozzle portion of the dispensing device; and  
at least one second support member for holding a container, the at least one first and second support members being spaced from each other in substantial axial alignment and connected to a frame member for connection to a supporting structure, the frame member including at least one third support member for the dispensing device, the frame member further including at least one side portion connected to the at least one third support member with the at least one side portion angling inwardly in a direction from the at least one third support member

**U.S. Serial No. 10/710,306**

**Atty. Docket No.: JD-327A-US**

Examiner: Steven J. Ganey

Art Unit No.: 3752

Page 9 of 12

toward the at least one first support member and wherein the at least one side portions are constructed and arranged to accommodate containers of different sizes.